AMENDMENTS TO THE CLAIMS:

Please replace the listing of claims presently on file by following new listing of claims:

Listing of Claims:

- 1. (Currently amended) A free flowing dry back-up insulating material having a thermal conductivity ranging between about 0.8 and about 1.8 [[BTU- in /F-h/pi²]]BTU·in/ft²·hr.·°F and a setting temperature lower than 400°F, wherein said material consists essentially of:
 - [[-]]a) from 67 to 96% by weight of fly-ash [[consisting
 of]] comprising cenospheres,
 - [[-]]b) from 2 to 15% by weight of a heat sensitive binder selected from the group consisting of boric acid and anhydrous boron oxide;
 - [[-]]c) from 2 to 7% by weight of a non-wetting agent selected from the group consisting of calcium fluoride, magnesium fluoride and barium sulphate;
 - [[-]]d) from 0 to 10% by weight of a heat expandable material selected from the group consisting of vermiculite and graphite; and
 - [[-]]e) from 0 to 1% by weight of a dust suppressant.
 - (Cancelled).

2

- 3. (Currently amended) The material of claim 1, wherein said material consists essentially of:
 - [[-]]a) from about 89.5% to 90% by weight of said fly ash;
 - [[-]]b) about 8% by weight of said heat sensitive binder;
 - [[-]]c) about 2% by weight of said non-wetting agent; and
 - [[-]]d) from about 0 to 0.5% by weight of said dust suppressant.
 - 4. (Cancelled).
- 5. (New) The material of claim 1, wherein said binder is boric acid.
- 6. (New) The material of claim 1, having a thermal conductivity of up to 1.42 BTU°in/ft.2°hr.°°F.
- 7. (New) The material of claim 1, which is free of organics.
- 8. (New) The material of claim 1, wherein said binder is anhydrous boron oxide.
- 9. (New) The material of claim 1, which comprises 2 to 5 wt% of calcium fluoride.
- 10. (New) The material of claim 1, which comprises kerosene as a dust suppressant.
- 11. (New) The material of claim 1, having a density of from 25 to 30 lb/ft. 3 .

3

Docket No.: <u>4715-006</u>

12. (New) The material of claim 7, which is free of organic binders.

13. (New) The material of claim 1, which further consists of TiO_2 and Fe_2O_3 .